



Alfa 250-IVN

Receipt Printer



Multiple interface choice



1. USB
2. Serial port
3. Ethernet
4. Cash drawer
5. power

- Compatible with EPSON ESC/POS and STAR command sets;
- Support paper near end and black mark detection;
- Connect and printer faster, stop Receipt misprinting;
- Support connecting to WLAN printing;
- Virtual serial port mode, USB port support OPOS application;
- 250mm/sec ultra high print speed;
- Built in Web page to set up printer directly;
- High speed driver printing mode,66% improvement in print;
- Serial + USB + Ethernet
- Support IP change via Serial or USB port.

SPECIFICATIONS AT A GLANCE

Print method

Direct thermal printing

Emulation

Compatible to ESC/POS

Paper width

79.5±0.5mm

Print width

72mm

Dot density

576 dots/line; 512 dots/line

Paper roll

80mm width, 83mm diameter max

Print speed

250mm/sec max

Paper thickness

0.06~0.08mm

Interface

Serial+ USB+ Ethernet

Character Size

ANK Font

Font A: 12×24dots Font B: 9×17dots

Data buffer

128K bytes

Barcode type

UPC-A /UPC-E /JAN13(EAN13) /JAN8(EAN8) /CODE39 /ITF
/CODEBAR /CODE93 /CODE128 / QR Code

Power

Power supply output: DC24V/2.5A

Power supply input: AC 110V/220V, 50-60HZ

Power input: DC 24/2.5A

Cash drawer: DC24V/1A

Work environment

Humidity:10 ~ 80% , Temperature:0 ~ 45 C

Storage environment

Humidity:10 ~ 90% , Temperature:-10 ~ 60 C

Print head life

150KM

Auto cutter life

1.5 million cuts

Operating system

Windows X86 / X64 / Linux / OPOS driver;

Net Weight

1.3kg

Dimension

152×200×138mm (W x L x H)



www.alfa-egy.com

