



Alfa B-555

Barcode Printer



Features

Label printing and receipt printing two-in-one

2~5 inch/s high-speed printing

With U disk function

2 in 1 Combo: Barcode label and receipt printer

Compatible with ESC and TSC command

SPECIFICATIONS AT A GLANCE

Printing mode	Thermal Label Printing	Thermal Receipt Printing
Dot density	203dpi	384dot/line
Print width	56mm max.	48mm
Print speed	101~ 127mm/sec	90mm/sec
Buffer	Dram: 2M, Flash: 2M	Dram: 2M, Flash: 2M
Print head temperature detect	thermal sensitive resistance	thermal sensitive resistance
Print head position detect	Micro switch	Micro switch
Paper sensor	Photo electricity	Photo electricity
Barcode type	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2/EAN8+5/CODEBAR/P OSTNET/UPC-A/ UPCA+2 /UPCA+5/UPC-E/UPCE+2/UPC-E+5/CPOST/MSI/MSIC/PLESSEY/ITF 14/EAN14	UPC-A/UPC-E /JAN13(EAN13) /JAN8/CODE39/CODEBAR/ITF/CODE93/CODE128
Interface	Serial + USB	Serial + USB
Paper type	Thermal paper roll / adhesive thermal paper	
Paper width	20~60mm	20~60mm
Paper diameter	110mm max .	110mm max .
Paper cutting method	Tear off	Tear off
Input	DC12V/4A	DC12V/4A
Cash drawer output	DC12V/1A	DC12V/1A
Work environment	5~45°C,	5~45°C,
Storage environment	0-10~50°C	0-10~50°C
Dimension	220x110x160mm (LxWxH)	220x110x160mm (LxWxH)
Weight	1.1kg	1.1kg



www.alfa-egy.com

